

AMENDMENTS TO THE CLAIMS

Claim 1. (currently amended) A solid state image device in which solid state image elements of N lines in a vertical direction and M pixels in a horizontal direction are arranged in a matrix shape, said solid state image elements being grouped in sets of red, green and blue colored pixels; said solid state image device comprising:

display means for displaying a position of a defective pixel occurred in said solid state element on a screen, a horizontal cursor operated in the vertical direction on said screen and displayed in white, and a vertical cursor operated in the horizontal direction on said screen and displayed in red, green or blue based on the color of the defective pixel at said position and flickering if the defective pixel is not previously known;

position selection means for selecting a position of a defective pixel on a screen of said display means, the position selection means having a manual writing mode and an automated writing mode; in said automated writing mode the position of said defective pixel is automatically determined by scanning an acquisition image acquired by said solid state image device and comparing a luminance value for each pixel with a predetermined luminance value, and

memory means for recording positional information of said defective pixel selected by said position selection means.

Claim 2. (original) A solid state image device according to claim 1, wherein said position selection means has,

horizontal cursor operated in vertical direction on a screen of said display means, vertical cursor operated in horizontal direction on said screen, and

writing determination button operated so as to be pressed at an intersection of said horizontal cursor and vertical cursor.

Claims 3-5. (canceled)

Claim 6. (original) A solid state image device according to claim 1, wherein a writing area from first line to the N line is assigned so as to previously write positional information of defective pixels of m pieces portion per one line, and it is performed so that positional information of a defective pixel occurred on the relevant line of said solid state image element is recorded in a writing area corresponding to the relevant line of said memory means.

Claim 7. (original) A solid state image device according to claim 1, wherein defect detection means for detecting positional information of a defective pixel occurred on the relevant line of said solid state image element, and

information writing and reading means for recording positional information of a defective pixel detected by said defect detection means in a writing area of said memory means corresponding to the relevant line and reading positional information from said writing area are provided.

Claim 8. (original) A solid state image device according to claim 1, wherein information rewriting means for deleting positional information of a defective pixel recorded in said memory means and rewriting the relevant positional information is provided.

Claim 9. (original) A solid state image device according to claim 1, wherein in said defect detection means,

line scanning in turn a solid state image element of N lines and M pixels and measuring luminance by respective solid state image element in a state where an incident light to said solid state image element is intercepted,

comparing respective luminance by said solid state image element and reference luminance previously set, and

detecting positional information of a defective pixel occurred on the relevant line corresponding to said comparative results.

Claim 10. (original) A solid state image device according to claim 1, wherein as for image acquisition information of a solid state image element of a defective pixel recorded in said memory means, at least defect correction means for interpolating image acquisition information of a solid state image element of said defective pixel is provided based on image acquisition information by solid state image elements in front and in the rear of said defective pixel.

Claim 11. (currently amended) A defective pixel recording method in a solid state image device in which solid state image elements of N lines in a vertical direction and M pixels in a horizontal direction are arranged in a matrix shape, wherein said solid state image elements are grouped in sets of red, green and blue colored pixels; comprising the steps of:

displaying a position of a defective pixel occurred in said solid state image element on a screen, a horizontal cursor operated in the vertical direction on said screen and displayed in white, and a vertical cursor operated in the horizontal direction on said

screen and displayed in red, green or blue based on the color of the defective pixel at said position and flickering if the defective pixel is not previously known;

selecting a position of a defective pixel displayed on said screen, including an automated writing mode in which the position of said defective pixel is automatically determined by scanning an acquisition image acquired by said solid state image device and comparing a luminance value for each pixel with a predetermined luminance value, and

recording positional information of said selected defective pixel in memory means.

Claim 12. (original) A defective pixel recording method of a solid state image device according to claim 11, wherein when a position of a defective pixel displayed on said screen is selected,

displaying horizontal cursor and vertical cursor on said screen simultaneously, manually operating not only said horizontal cursor in vertical direction and manually operating but also said vertical cursor in horizontal direction, and

determining a writing by superimposing an intersection of said horizontal cursor and vertical cursor on a position of said defective pixel.

Claim 13. (original) A defective pixel recording method of a solid state image device according to claim 11, wherein when a defective pixel which is larger than a defective pixel recorded in said memory means, is detected positional information of a defective pixel recorded in said memory means is deleted and rewritten into new positional information .

Claim 14. (original) A defective pixel recording method of a solid state image device according to claim 11, wherein when positional information of said defective pixel is recorded in memory means,

preparing a writing area from first line to Nth line in said memory means so as to previously write defective pixels of m pieces portion per one line, and

subsequently, recording positional information of a defective pixel occurred on the relevant line of said solid state image element in a writing area of said memory means corresponding to the relevant line.